



RECOMMENDED P.C.B LAYOUT(TOP VIEW)
TOLERANCE: ±0.05

- MATERIALS**
- 1.HOUSING: L.C.P. (UL 94V-0), BLACK
 - 2.TERMINAL: BRASS (C2680), GOLD PLATING 1μ Min. ON CONTACT AREA, WHITE TIN 80μ Min. PLATING ON SOLDER TAIL, UNDER NICKEL PLATING 50μ Min OVER ALL.
 - 3.SHELL: S50C, NICKEL PLATING 50μ Min.
- SPECIFICATION**
- 1.CURRENT RATING : 0.5 A MAX.
 - 2.DIELECTRIC WITHSTANDING VOLTAGE : 500V AC R.M.S.
 - 3.INSULATION RESISTANCE : 100M OHMS MIN.
 - 4.CONTACT RESISTANCE : 30m OHMS MAX.
 - 5.OPERATING TEMPERATURE : -20°C TO +85°C.
 - 6.INSERTION FORCE : 4.5gf MAX.
 - 7.EXTRACTION FORCE : 1.0~4.0gf MIN.
 - 8.SALT SPRAY : 24 HOURS PASS.
 - 9.REFLOW SOLDERING(SMD COMPONENT) OVEN
 - 10.TEMPERATURE: 260°C.5SEC

SHENZHEN VISTAR ELECTRONICS CO., LTD.

UNITS: mm		TITLE:	
X	±0.5	DP180度SMT13.0脚 脚长3.0+弹片	
X	±0.38	APPD:	PART NO.
XX	±0.25	CHIKD:	DP-F06B-13H
XXX	±0.15	DR:	SCALE SHEET REV.
ANGLB	±3°	Luoyu	8/7'19 N/A 1/1 AO

REV.	ECON. NO.	DESCRIPTION	DRAWN	DATE
AO	---	DRAWING RELEASE		